- 1 -

A SYSTEM FOR DAMPING THERMO-ACOUSTIC INSTABILITY IN A
COMBUSTOR DEVICE FOR A GAS TURBINE

TECHNICAL FIELD

5   The present invention relates to a system for damping
thermo-acoustic instability in a combustor device
comprising at least one combustion chamber and at least
one burner associated to said combustion chamber and
designed to serve a gas turbine, which uses passive
10 damping means, in particular Helmholtz resonators.

BACKGROUND ART

It is known that, to achieve increasingly higher
efficiency in gas turbines, in particular latest-
15 generation ones, it is necessary both to use
increasingly higher start-of-expansion temperatures and
to obtain, in the most efficient way possible, an
optimal homogeneity of temperature on the blades. Said
results can be achieved and, in actual fact, are
20 currently achieved, using combustion chambers with
annular geometry.

The aforementioned combustion chambers enable excellent
performance both as regards efficiency of combustion and
25 as regards the limitation of pollutant emissions and the
high density of thermal yield (MWth/m^3). However, on the
basis of the results of some verifications, it may be
stated that the annular geometry associated to high
densities of thermal yield can favour onset of phenomena
30 of thermo-acoustic instability. The latter occur with
marked oscillations of pressure within the combustion
chamber, at well-defined frequencies that are
characteristic of the geometry of the combustor and of
the running conditions. Said oscillations can bring
35 about undesirable vibrations in the turbine and damage
its components.

- 2 -

To limit this problem, manufacturers of gas turbines have developed various techniques.

5   Some techniques are based upon decoupling of the forcing frequencies, generated by the peculiarities of the burner, from the natural frequencies of the mechanical system that enters into vibration. Other techniques are based upon control of the fuel in phase opposition with

10   the onset of the pressure oscillations (active control). However, these methods, which are prevalently of an active type, have moving members and/or need to undergo operations of control and adjustment during the operating cycle of the gas turbine.

15

Also known are passive-damping systems, based upon the use of dissipater devices, in particular Helmholtz resonators, which capture the acoustic waves and dampen their amplitude, dissipating the energy thereof.

20

For example, the U.S. patent No. 6,530,221 relates to a system in which the dissipaters used are not Helmholtz resonators, but perforated box-section elements. A dissipater element of this type can give rise to the

25   following problems:
1) the blades of the turbine may suffer damage in the case where one of the box-section elements is damaged on account of vibrations; and
2) application of the box-section elements is possible

30   only on combustors of a cannular type and not on annular ones, in so far as, in the solution provided by the patent, the resonator is mounted on the can.

The U.S. patent No. 6,530,221 describes the use of a

35   resonator device for application of which it is necessary to redesign the air chamber (i.e., a casing

- 3 -

which surrounds the combustion chamber and delivers thereto the air for supporting combustion) and the combustion chamber. The mechanism for regulating the volume of the resonator proves moreover very delicate.

5

The British patent application GB 2 288 660 A describes a system in which the resonators used are classic Helmholtz resonators, sized according to relations available in the literature. However, the position in
10 which the resonators should be mounted on the combustion chamber to be effective is not clarified. Furthermore, the volume of the resonator is not adjustable, so that the operating frequency is fixed. In order to overcome this drawback, the resonators are provided with a
15 complicated system for regulation of the internal temperature so as to be able to regulate the frequency according to the temperature. In theory, the system is flexible, but at the expense of complications in terms of plant design and instrumentation, which limits the
20 reliability thereof in an environment that is particularly critical, as regards temperature and pressure, as is that of a gas turbine.

Finally, the European patent application
25 No. 0 597 138 A1 describes the application of a Helmholtz resonator to an annular combustion chamber, said resonator being mounted on the side of the combustion chamber ("upstream" portion or "front plate") that carries the burner or burners. Hereinafter, the
30 terms "upstream" and "downstream" are intended as referring to the direction of flow of the burnt gases in the combustion chamber.

Also in this case, the volume of the resonator is not
35 adjustable, so that the operating frequency is fixed. Consequently, if the range of frequencies in which the

- 4 -

resonator is effective is very restricted, as proves
likely from the drawings (a range which, however, in
this document is not defined, even indirectly), the
damping could be insufficient in various operating
5   conditions. Furthermore, the position of installation
chosen for the resonator, as has been experimentally
found by the technicians of the present applicant, is
not the optimal position for its operation. In addition,
for reasons of encumbrance, application of the resonator
10 in the way indicated in EP 0597138A1 is not possible on
combustion chambers different from the one hypothesized:
for example, in the case of the majority of known
turbines it would be necessary to redesign the air
chamber and the combustion chamber.

15

Finally, it is to be highlighted that all the known
solutions described above do not define the range of
frequencies in which the resonator is effective, nor the
effectiveness of damping of the pressure waves.
20 Consequently, the state of the art that illustrates the
application of passive resonators/dampers to combustion
chambers of gas turbines in practice merely provides
nothing but speculations as regards the possible
effectiveness of the solutions proposed, without in
25 effect providing to the person skilled in the branch any
indication supported by experimental findings.

DISCLOSURE OF INVENTION
A purpose of the present invention is to provide a
30 system for damping thermo-acoustic instability in a
combustor device for a gas turbine which will be free
from the drawbacks described and will be of proven
effectiveness.

35 Another purpose of the invention is to provide a system
for damping thermo-acoustic instability in a combustor

- 5 -

device for a gas turbine that will be of contained
overall dimensions and, in general, such as to enable
application thereof to any annular combustion chamber of
a known type, that will enable ease of installation and
5 maintenance, contained costs, high reliability and a
structure such as to enable a simple and fast regulation
of the volume of the resonator or resonators.

According to the invention there is hence provided a
10 system for damping thermo-acoustic instability in a
combustor device for a gas turbine according to what is
defined in Claim 1.

In practice, the system for damping thermo-acoustic
15 instability according to the invention can be used on
combustors that include a combustion chamber of an
annular type and a plurality of burners associated to
the combustion chamber and mounted in a position
corresponding to a front upstream portion of the
20 combustion chamber, where the term "upstream", as
likewise the term "downstream", used here and in what
follows, are to be understood as referring to the
direction of flow of burnt gases traversing the
combustion chamber, for example directed towards the
25 first stage of a gas turbine served by the aforesaid
combustor device.

The damping system according to the invention comprises
a plurality of Helmholtz resonators, each of which
30 comprises a casing defining within it a pre-set volume
and a neck for hydraulic connection between said pre-set
volume and said combustion chamber. According to the
invention, said damping system is characterized in that
the necks are all connected to one side of the
35 combustion chamber distant from the front upstream
portion thereof provided with the burners, in particular

to a downstream portion of the combustion chamber.

Each resonator is placed asymmetrically in a circumferential position around the combustion chamber, housed within a supporting combustion air delivery casing set outside an annular body delimiting the combustion chamber itself. Preferably, the casing of each resonator comprises means for delivery of a cooling fluid consisting of a plurality of asymmetrical through holes made in an end plate of the casing, which is set facing the side opposite to the combustion chamber and through which a part of air for supporting combustion is conveyed towards the combustion chamber through the pre-set volume and the neck of each resonator.

Preferably, the casing of each resonator comprises means for regulation of said pre-set volume, according to which the casing comprises two cup-shaped tubular bodies, which are mounted in a telescopic way co-axially on one another, with respective concavities facing one another, by means of a threaded coupling. A threaded ring-nut is designed to act as locknut for selective blocking of the two tubular bodies in a plurality of different relative axial positions, in which one is more or less screwed on the other.

In this way, the invention surprisingly achieves the purposes outlined above. In fact, the geometry described maximizes the range of frequencies which can be dampened, rendering unnecessary the adoption of any "active" feedback control system, which could reduce the reliability of the system. Furthermore, said range of frequencies that can be dampened can be easily regulated as a function of the fuel used and other operating parameters which can vary case by case, in the step of starting of the gas turbine, simply by varying just once

the pre-set volume defined internally by each resonator casing.

The system according to the invention hence presents the
5 following advantages:
    • it overcomes the limits of the known art, referred to previously, because it does not have any moving members nor does it need any control/regulation;
    • the resonators are of a very simple and economically
10 advantageous mechanical construction and do not call for any particular technology;
    • installation of the resonators is particularly simple; and
    • introduction of the resonators into an existing
15 combustor device does not interfere in the least with the combustion stoichiometry, the fluid-dynamics, or the global performance of the combustor and, consequently, does not require any verification or modification thereof.
20

BRIEF DESCRIPTION OF THE DRAWINGS
Further purposes and advantages of the present invention will emerge clearly from the ensuing description of a non-limiting embodiment thereof, which is provided
25 merely as an example, with reference to the figures of the annexed drawings, in which:
    - Figure 1 is a schematic longitudinal sectional view of a combustor device for a gas turbine (known and not illustrated) provided with the system for damping
30 thermo-acoustic instability according to the invention;
    - Figure 2 is a top plan view, at an enlarged scale, of a resonator forming part of the system for damping thermo-acoustic instability according to the invention;
    - Figure 3 is a view sectioned according to the plane
35 III-III of the resonator of Figure 2; and
    - Figure 4 is a graph that summarizes comparative

- 8 -

experimental results of studies carried out on one and the same turbine and one and the same combustor, respectively with and without the system for damping thermo-acoustic instability of the invention.

5

BEST MODE FOR CARRYING OUT THE INVENTION

With reference to Figures 1, 2 and 3, designated as a whole by 1 is a system for damping thermo-acoustic instability in a combustor 2 for a gas turbine of any
10 known type and consequently not illustrated for reasons of simplicity. The combustor device comprises a combustion chamber 4 of an annular type, having an axis of symmetry A which coincides with the axis of rotation of the aforesaid gas turbine (not illustrated). A
15 portion 5 set downstream with respect to a flow 6 of burnt gases (indicated by the arrow) of the combustion chamber 4 is connected (in a way that is known and is not illustrated) with at least one expansion stage of the aforesaid turbine. At least one burner 7
20 (illustrated only schematically) of any known type, is associated to the combustion chamber 4, in the case in point mounted in a position corresponding to a front upstream portion 8 of the combustion chamber 4.

25 In the case in point, the combustion chamber 4, which is delimited by an annular body 10, is served by a plurality of burners 7 (only one of which is illustrated for reasons of simplicity), carried symmetrically in a ring by an annular element 11 of the body 10 in a
30 position corresponding to the upstream portion 8 thereof.

The damping system 1 comprises at least one Helmholtz resonator 12, which in turn comprises a casing 13
35 defining inside it (Figure 3) an empty volume 14 having a pre-set size, and a neck 15 for hydraulic connection

between the volume 14 and the combustion chamber 4. According to the invention, the neck 15 is connected to one side of the combustion chamber 4 at a distance from the front upstream portion 8 thereof provided with the
5   burner or burners 7.

In particular, the damping system according to the invention comprises a plurality of Helmholtz resonators 12 (only one of which is illustrated for reasons of
10 simplicity and which, in what follows, will be indicated more briefly only as "resonators 12"), which are identical to one another and are mounted circumferentially in a ring in cantilever fashion on the annular body 10, with the respective necks 15
15 hydraulically connected to the downstream portion 5 of the combustion chamber 4. According to an aspect of the invention, the resonators 12 are mounted in positions that are asymmetrical with respect to one another, both in the radial direction and in the axial direction, with
20 reference to the axis of symmetry A. In other words, they are arranged circumferentially set at a distance apart from one another and axially at a distance from the burners 7, i.e., from the annular element 11 carrying said burners, with an irregularly varying
25 pitch.

The resonators 12 are housed within a case 16, known as "air chamber" or "air case" and illustrated only partially and schematically in Figure 1, for delivery of
30 air for supporting combustion. The air case 16 is set outside the annular body 10 and is shaped so as to be designed to feed air for supporting combustion directly to each burner 7, through the annular element 11.

35 The casing 13 and the neck 15 of each resonator 12 have a cylindrical symmetry and are arranged with respective

axes of symmetry thereof (in the case in point illustrated as coinciding with one another and designated by B in Figure 1) parallel to one another and oriented to form in the longitudinal section of Figure 1, a pre-set angle α, preferably substantially of 90°, with the direction of flow 6 of burnt gases that, in use, traverse the combustion chamber 4. This coincides with the direction of orientation of the axis of symmetry of each burner 7, designated by C in Figure 1.

According to a preferred aspect of the invention, the casing 13 of the resonators 12 comprises means for delivery of a cooling fluid, in the case in point consisting of a plurality of holes 18 of pre-set diameter made through the casing 13 and designed to enable passage of (a small) part of the air for supporting combustion directly from the delivery air case 16 towards the combustion chamber 4 through the pre-set volume 14 and the neck 15 of each of the resonators 12.

The holes 18 are made only through an end plate 20 of the casing 13, facing in use the side opposite to the combustion chamber 4, and are arranged in positions that are mutually asymmetrical, as may be clearly seen in Figure 2.

According to a further preferred aspect of the invention, the casing 13 of each of the resonators 12 comprises means for selectively varying the pre-set volume 14 within a pre-set range.

Said means for selectively varying the pre-set volume 14 of each resonator 12 consist of a particular structure of the casing 13 of the resonators 12, which comprises two cup-shaped tubular bodies 21, 22, which are mounted

in a telescopic way co-axially on one another (Figure
3), with respective concavities facing one another, by
means of a threaded coupling 23. A threaded ring-nut 24
is coupled outside on the tubular body 22 of smaller
5   diameter, which, in the non-limiting case illustrated
here, is the one set facing, in use, the body 10 and
which is consequently provided, in a single piece, with
the neck 15 and is provided on the outside with a male
part 23a of the threaded coupling 23. The threaded ring-
10 nut 24 is designed, in use, to bear axially upon the
tubular body 21 of larger diameter, which can be screwed
outside on the tubular body 22, thanks to a female part
23b of the threaded coupling 23, on the side opposite to
the combustion chamber 4.

15

The structure described of the casing 13 of each
resonator 12 enables in use, in particular during the
step of starting of the gas turbine and of the
corresponding plant, calibration of the natural
20 frequency of the resonator, which can thus be tuned to
the natural frequencies of the combustor 2 that are to
be dampened. In fact, said natural frequency is
determined by the size of the volume 14, as well as by
the number, diameter and length of the necks, number and
25 size of the holes 18, and by the mean temperature of the
gas present in the volumes 14 and in the necks 15, which
is a function also of the type of fuel used for
supplying the gas turbine. For more consolidated
applications, it is of course possible to build
30 resonators 12 with a fixed volume 14, in which the two
tubular elements 21, 22 are not relatively mobile.

In use, the air contained in the volumes 14 determines
the stiffness of the damping system. The holes 18 can
35 have diameters of between 1.5 mm and 4.5 mm and must be
present in a number such as to enable a good cooling of

- 12 -

the resonators 12, without altering the fluid-dynamics
of cooling of the refractory element present in the
combustion chamber 4.

5   To enable ease of manoeuvring of the tubular elements
21, 22, the outermost tubular element 21, fixed to the
plate 20, is provided, in a single piece, on its top end
portion, with a nut 25, which has the function of
tightening the tubular element 21 against the ring-nut
10   24, at the pre-set distance. The ring-nut 24 is screwed
onto the male part 23a of the threaded coupling 23 so as
to force connection thereof and to serve as a locknut.

The necks 15 are mounted in use so as to present their
15   own outlet ends inside the internal volume of the
combustion chamber 4, in the case in point of the
downstream portion 5 thereof. They can extend (Figure 3,
part illustrated hatched), in some cases, within the
pre-set volume 14 delimited by the coupled tubular
20   elements 21, 22 and, hence, beyond a plate 26 (Figure 3)
of the tubular element 22 which carries, integral in one
piece, the respective neck 15. Said configuration is
adopted in order to increase the resonant mass, given
the same overall dimensions along the axis B of the
25   resonator. The end of the neck 15 that impinges upon the
plate 26 at the base of the pipe is provided with means
for coupling to the body 10, for example projections or
else a threaded coupling 30.

30   The resonators, by their very nature, function most
efficiently when they are set in the proximity of the
areas with maximum acoustic pressure. However, the
angular position of said areas is not exactly
foreseeable in a simple way, in so far as the combustion
35   chamber has an axial symmetry.

- 13 -

Said angular position is moreover caused by the small
constructional differences of the burners.

On the other hand, the axial position of the peaks of
5   acoustic pressure is located in an area corresponding to
the area of transition, where the combustion reaction is
completed, but can be determined only empirically, using
a certain number of dynamic-pressure gauges, or else
constructed   theoretically   using   finite-element   or
10 boundary-element programs.

Experimental tests conducted by the present applicant
have made it possible to show that, to be effective, the
resonators must be positioned in an adequate number
15 along the circumference of the combustion chamber and,
preferably, their mutual arrangement must not present
axial symmetry. They must moreover be arranged in a
position corresponding to the downstream portion of the
combustion chamber or in any case in a position
20 corresponding to the side thereof at a greater distance
from the burners.

Finally, the present invention is further described by
the example appearing below.
25

Example of application

The   damping   system   presented   in   the   foregoing
description, with reference to the annexed plate of
drawings was tested in an experimental annular combustor
30 manufactured by the present applicant, where a number of
resonators   were   installed   in   conformance   with   the
drawing of Figure 3, said resonators being distributed
along the circumference of the combustion chamber in the
positions indicated in Figure 1. More in particular, the
35 annular combustor was connected to an existing (40-MWth)
boiler and was made up of the following components:

- 14 -

• a combustion chamber of a commercially available
AEN/SIE GT;

• twenty-four AEN/SIE hybrid burners;

• a natural-gas (NG) supply system for operating in
5 diffusion, premixing, and pilot modes; '

• an air supply from the fan of the boiler provided
with a pre-heater for pre-heating up to 350°C; and

• a chimney (the same as that of the boiler).

The instrumentation used comprised:

10 ♦ a meter for measuring the flow, pressure, and
temperature of each flow;

♦ a meter for measuring the difference in pressure (ΔP)
through the combustion chamber;

♦ two dynamic pressure transducers installed on the air
15 chamber;

♦ ten dynamic-pressure transducers installed in
appropriately selected positions of the combustion
chamber;

♦ two dynamic-pressure transducers installed on the
20 Helmholtz resonators; ..

♦ twenty-four thermocouples installed in a position
corresponding to the outlet of the exhaust gas; and

♦ samples of exhaust gas for carrying out chemical
analysis.

25

A data-acquisition system was installed, capable of
storing the static and dynamic synchronized data and of
performing calculation of Fourier transform (FFT) of
the signals for dynamic pressure.

30

A first series of tests was completed using the standard
configuration of the combustor in order to determine the
thermo-acoustic limits corresponding to different
boundary conditions. Then, a set of Helmholtz resonators
35 was installed, the resonators being spaced in an axial
and circumferential direction, and the thermo-acoustic

limits were studied again, using the same boundary
conditions and varying the internal volume of the
resonator in order to regulate the dampened frequencies.

5   A large data bank is available, containing the results
of the tests.

The aforementioned tests consisted in reproducing the
combustion conditions that occur under normal operation
10 of the gas turbine and as the parameters influencing,
above all, onset of thermo-acoustic instability were
then varied. These parameters were, basically, the flow
of air for supporting combustion and the flow of fuel.

15 On the basis of said tests, graphs were obtained, which
give, on the abscissa, the excess air (air flow/fuel
flow ratio) and, on the ordinate, the pressure
oscillation that is measured in the combustion chamber
(expressed in mbar), via particular piezoelectric
20 sensors. For each running condition tested (fuel flow of
the pilot flame, temperature of the air for supporting
combustion, flow of air for supporting combustion), a
curve of the type given in Figure 4 was obtained.

25 The above tests were carried out starting from
conditions of high stability, which occur for high
air/fuel ratios (AFRs). Next, the AFR was decreased
until the first oscillations in the combustion chamber
occurred (sharp rise in the mbar measured). Once the
30 condition of instability was reached, the AFR was
increased until stable conditions were restored. It was
noted that the phenomenon presents a hysteresis; i.e.,
the instability does not disappear at the same AFR value
at which it appeared, but it is necessary to go to
35 significantly higher values. This behaviour emerges
clearly from Figure 4, where the cycles of hysteresis

- 16 -

measured both in the presence of resonators and in the
absence thereof are compared.

The results of the tests show that the presence of the
5   resonators arranged in the way indicated enables
operation the gas turbine down to very small values of
AFR; i.e., the range of stability of the combustor is
enlarged significantly.

10